

# HS United European Connectors

Flachsteckhülse 2,8 mm mit Rastpunkt	Artikel-Nr.	Leiter- quer- schnitt mm <sup>2</sup>	Material	Ober- fläche	Steck- dicke mm	L1 mm	L2 mm	Mat- erial- stärke mm	Verp.- Ein- heit
Längstransport	22.824.110.003	0,25 – 0,5	CuZn	blank	0,3	8	3,6	0,25	25.000
	22.824.120.003		CuZn	Sn					
	22.824.310.003		CuSn	blank					
	22.824.320.003		CuSn	Sn					
	22.824.110.004	0,25 – 0,5	CuZn	blank	0,4	8	3,6	0,25	25.000
	22.824.120.004		CuZn	Sn					
	22.824.310.004		CuSn	blank					
	22.824.320.004		CuSn	Sn					
	22.824.110.005	0,25 – 0,5	CuZn	blank	0,5	8	3,6	0,25	25.000
	22.824.120.005		CuZn	Sn					
	22.824.310.005		CuSn	blank					
	22.824.320.005		CuSn	Sn					
	22.824.110.008	0,25 – 0,5	CuZn	blank	0,8	8	3,6	0,25	25.000
	22.824.120.008		CuZn	Sn					
	22.824.310.008		CuSn	blank					
	22.824.320.008		CuSn	Sn					
Flachsteckhülse 2,8 mm ohne Rastpunkt	Artikel-Nr.	Leiter- quer- schnitt mm <sup>2</sup>	Material	Ober- fläche	Steck- dicke mm	L1 mm	L2 mm	Mat- erial- stärke mm	Verp.- Ein- heit
Längstransport	22.824.112.003	0,25 – 0,5	CuZn	blank	0,3	8	3,6	0,25	25.000
	22.824.122.003		CuZn	Sn					
	22.824.312.003		CuSn	blank					
	22.824.322.003		CuSn	Sn					
	22.824.112.004	0,25 – 0,5	CuZn	blank	0,4	8	3,6	0,25	25.000
	22.824.122.004		CuZn	Sn					
	22.824.312.004		CuSn	blank					
	22.824.322.004		CuSn	Sn					
	22.824.112.005	0,25 – 0,5	CuZn	blank	0,5	8	3,6	0,25	25.000
	22.824.122.005		CuZn	Sn					
	22.824.312.005		CuSn	blank					
	22.824.322.005		CuSn	Sn					
	22.824.112.008	0,25 – 0,5	CuZn	blank	0,8	8	3,6	0,25	25.000
	22.824.122.008		CuZn	Sn					
	22.824.312.008		CuSn	blank					
	22.824.322.008		CuSn	Sn					