

HS United European Connectors

Flachsteckhülse 4,8 mm leicht steckbar	Artikel-Nr.	Leiter- quer- schnitt mm ²	Material	Ober- fläche	Steck- dicke mm	L1 mm	L2 mm	Mat- erial- stärke mm	Verp.- Ein- heit
Längstransport	74.810.115.001	0,5 – 1,0	CuZn	blank	0,5	16	6	0,3	12.000
	74.810.125.001		CuZn	Sn					
	74.810.315.001		CuSn	blank					
	74.810.325.001		CuSn	Sn					
	74.810.110.001	0,5 – 1,0	CuZn	blank	0,8	16	6	0,3	12.000
	74.810.120.001		CuZn	Sn					
	74.810.310.001		CuSn	blank					
	74.810.320.001		CuSn	Sn					
	74.820.115	2 x 0,75	CuZn	blank	0,5	16	6	0,3	10.000
	74.820.125		CuZn	Sn					
	74.820.315		CuSn	blank					
	74.820.325		CuSn	Sn					
	74.820.110	2 x 0,75	CuZn	blank	0,8	16	6	0,3	10.000
	74.820.120		CuZn	Sn					
	74.820.310		CuSn	blank					
	74.820.320		CuSn	Sn					
74.825.115	1,0 – 2,5	CuZn	blank	0,5	16	6	0,3	10.000	
74.825.125		CuZn	Sn						
74.825.315		CuSn	blank						
74.825.325		CuSn	Sn						
74.825.110	1,0 – 2,5	CuZn	blank	0,8	16	6	0,3	10.000	
74.825.120		CuZn	Sn						
74.825.310		CuSn	blank						
74.825.320		CuSn	Sn						